

BSC series for filling of bored piles

BSC 1005 D3B

Concrete pressure up to 71 bar
Output up to 58 m³/h



Note: This is a merely informative, non-binding document. Maximum theoretical values listed. Specifications are subject to change without prior notice. Photos and drawings are for illustrative purposes only. For available options, please consult the factory.

Technical data

Dimensions		
Length	mm	5,523
Width	mm	2,018
Height	mm	2,433
Weight	kg	5,000
Concrete pump		
Output up to	m ³ /h	58
Concrete pressure up to	bar	71
Pump strokes	1/min	34
Delivery cylinder stroke	mm	1,000
Delivery cylinder diameter	mm	180
Pressure connection	m	5.5" (125)

Hopper		
Capacity	l	350
Max. noise level	dB	108
Central lubrication		
Rubber collar		
Chassis		
Engine Diesel Deutz, 6 cylinders		
Engine power	kW (HP)	55 (75)
Engine emissions Stage III B / Tier 4f		
Steel crawlers, TFW-Fahrtechnik		
Max. speed	km/h	2
Diesel tank	l	135
Lights 2 on the hopper, 1 in front		

Technical data

Remote control		
Radio remote control (transport and output)		
Cable remote control (output)		
Cable length	m	10
Cleaning equipment		
Water tank	l	762
Cleaning pump	l/min /bar	50 / 20
Air compressor	l/min	860
Pressured air tank	l	40
Safety platform		
Accessories		

Others		
Standard coat of paint MB 1227 Yellow		
Technical documents 1 paper copy, 1 CD-ROM		
Tool box		
Emergency button		

Optionals

Automatic central lubrication

Electric vibrator

Transport dimensions

